# NSN 5930-01-150-1647

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-150-1647

## **Body Style:**

Hole mounted

## Hazardous Locations/environmental Protection:

Salt spray resistant

## Case Material:

Metal

#### Actuator Length:

1.562 inches

#### Actuator Style:

Roller arm

#### Actuator Height:

1.562 inches

#### Actuator Roller Diameter:

0.750 inches

#### Actuator Roller Width:

## 0.310 inches

Housing Height:

2.562 inches

## Housing Length:

3.688 inches

## Housing Width:

2.000 inches

#### Center To Center Distance Between Housing Mounting Facilities Parallel To Height:

1.812 inches

## Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

1.938 inches

#### Maximum Voltage Rating In Volts:

480.0 ac and 250.0 dc

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Unthreaded hole

#### **Nonpile-up Contact Arrangement:**

1 pole, double throw, two positions momentary single switch unit

#### Switch Actuating Force:

Between 8.0 inch-ounces and 20.0 inch-ounces

## **Actuator Movement:**

0.219 pretravel inches and 90.0 overtravel degrees and 0.007 differential inches

## Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

## Terminal Type And Quantity:

3 screw

# NSN 5930-01-150-1647

Sensitive Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

