# NSN 5930-01-150-1660

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-150-1660

## **Thread Class:**

2b single mounting facility

# Hazardous Locations/environmental Protection:

Dustproof

# **Overall Length:**

3.500 inches

## **Overall Height:**

3.688 inches

## **Overall Width:**

4.375 inches

#### Shaft Diameter:

0.375 inches single actuator

## Shaft Length:

1.250 inches single actuator

## Individual Section Quantity:

2

## Knob Manufacturer Code:

82121

## Knob Manufacturer Part Number:

А

## Longest Horizontal Distance Between Mounting Centers:

2.281 inches single mounting facility

# Longest Vertical Distance Between Mounting Centers:

2.281 inches single mounting facility

## Switch Contact Basic Design:

Nonpile-up symmetrical

## **Pole Quantity:**

1 each section rear

## Throw Quantity:

2 each section rear

## **Mounting Method:**

Threaded hole single mounting facility

#### Features Provided:

Actuator knob

## Thready Qty Per Inch (tpi):

20 single mounting facility

## **Thread Size:**

0.250 inches single mounting facility

## **Contact Voltage Rating In Volts:**

500.0 highest ac voltage rating at sea level

## Mounting Facility Pattern:

Four position rectangular single mounting facility

# NSN 5930-01-150-1660

Rotary Switch - Page 2 of 2



## Switch Actuator Indexing Position Quantity:

2 single actuator

#### Shaft Type:

Round single actuator

## Terminal Type:

Tab w/screw

## **Contact Switching Action:**

Breaks before makes each section rear

## **Switch Actuator Positioning Increment:**

180.0 degrees single actuator

#### Switch Actuator Stop Device Type:

Fixed stop single actuator

#### **Contact Load Current Rating:**

40.0 amperes resistive load lowest ac voltage rating at sea level

#### **Special Features:**

Round threaded hole shaft

#### Style Designator:

Tap, circuit selector

## **Thread Series Designator:**

Unc single mounting facility

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

#### Fiig:

A052b0