NSN 5930-01-150-4586

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-150-4586

| Body Style: |
|--|
| Hole mount |
| Hazardous Locations/environmental Protection: |
| Watertight |
| Overall Length: |
| 3.125 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 3.000 inches |
| Overall Width: |
| 3.750 inches |
| Body Width: |
| 3.750 inches |
| Body Height: |
| 6.250 inches |
| Case Material: |
| Metal |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 5.500 inches |
| Switch Actuator Quantity: |
| 2 |
| Actuator Style: |
| Round, flush |
| Actuator Color: |
| Amber 1st actuator |
| Actuator Inscription: |
| Open 2nd actuator |
| Maximum Voltage Rating In Volts: |
| 440.0 ac and 250.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Features Provided: |
| Actuator seal |
| Nonpile-up Contact Arrangement: |
| 2 pole, single throw, normally closed, double break, momentary action single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 0.500 amperes inductive dc and 5.000 amperes inductive ac |
| Terminal Type And Quantity: |
| 6 screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

--

NSN 5930-01-150-4586

Push Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0