## NSN 5930-01-150-6420

**Hazardous Locations/environmental Protection:** 

Rotary Switch - Page 1 of 2

Watertight

Overall Length: 3.520 inches



View Online at https://aerobasegroup.com/nsn/5930-01-150-6420

| Overall Height:  |
|--|
| 1.740 inches   |
| Overall Width:   |
| 2.120 inches   |
| Unthreaded Mounting Hole Diameter:                                       |
| 0.189 inches single mounting facility                                    |
| Individual Section Quantity:   |
| 1  |
| Knob Manufacturer Code:  |
| 27192  |
| Knob Manufacturer Part Number:   |
| 53-1160  |
| Knob Specificationial Markings:  |
| Off eosc run   |
| Longest Horizontal Distance Between Mounting Centers:                    |
| 1.620 inches single mounting facility                                    |
| <b>Longest Vertical Distance Between Mounting Centers:</b>               |
| 1.250 inches single mounting facility                                    |
| Switch Contact Basic Design:   |
| Nonpile-up nonsymmetrical  |
| Mounting Method:   |
| Unthreaded hole single mounting facility                                 |
| Features Provided:   |
| Actuator knob  |
| Contact Voltage Rating In Volts:   |
| 440.0 highest ac voltage rating at sea level                             |
| Mounting Facility Pattern:   |
| Four position rectangular single mounting facility                       |
| Switch Actuator Indexing Position Quantity:                              |
| 2 single actuator  |
| Terminal Type:   |
| Tab w/screw  |
| Contact Load Current Rating:   |
| 750.0 milliamperes resistive load highest ac voltage rating at sea level |
| Style Designator:  |
| In-line, cam actuated  |
| Shelf Life:  |
| N/a  |

## **NSN 5930-01-150-6420** Rotary Switch - Page 2 of 2



|  | Of |  |  |  |
|--|----|--|--|--|

Demilitarization:

No

Fiig:

A052b0