Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-150-8327

Hazardous Locations/environmental Protection:
Watertight
Overall Length:
3.520 inches
Overall Height:
1.740 inches
Overall Width:
2.120 inches
Unthreaded Mounting Hole Diameter:
0.189 inches single mounting facility
Individual Section Quantity:
2
Knob Manufacturer Code:
27192
Knob Manufacturer Part Number:
53-1160
Knob Specificationial Markings:
Normal stop
Longest Horizontal Distance Between Mounting Centers:
1.620 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
1.250 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Method:
Unthreaded hole single mounting facility
Features Provided:
Actuator knob and cam actuated
Contact Voltage Rating In Volts:
440.0 highest ac voltage rating at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Cam Actuated Switch Contact Arrangement:
1 pole, single throw, both positions maintained each switch each section in-line
Switch Actuator Indexing Position Quantity:
1 single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section in-line
Contact Load Current Rating:
750.0 milliamperes resistive load highest ac voltage rating at sea level

## NSN 5930-01-150-8327

Rotary Switch - Page 2 of 2

Style Designator:

In-line, cam actuated

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0

