

View Online at <https://aerobasegroup.com/nsn/5930-01-150-8327>

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

3.520 inches

**Overall Height:**

1.740 inches

**Overall Width:**

2.120 inches

**Unthreaded Mounting Hole Diameter:**

0.189 inches single mounting facility

**Individual Section Quantity:**

2

**Knob Manufacturer Code:**

27192

**Knob Manufacturer Part Number:**

53-1160

**Knob Specificational Markings:**

Normal stop

**Longest Horizontal Distance Between Mounting Centers:**

1.620 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

1.250 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Unthreaded hole single mounting facility

**Features Provided:**

Actuator knob and cam actuated

**Contact Voltage Rating In Volts:**

440.0 highest ac voltage rating at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Cam Actuated Switch Contact Arrangement:**

1 pole, single throw, both positions maintained each switch each section in-line

**Switch Actuator Indexing Position Quantity:**

1 single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section in-line

**Contact Load Current Rating:**

750.0 milliamperes resistive load highest ac voltage rating at sea level

**Style Designator:**

In-line, cam actuated

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0