NSN 5930-01-150-8637



Sensitive Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-150-8637 **Thread Class:** 2b **Body Style:** Hole mounted **Overall Length:** 2.600 inches **Center To Center Distance Between Mounting Facilities Parallel To Length:** 1.000 inches **Overall Height:** 3.980 inches **Overall Width:** 0.812 inches **Body Length:** 1.938 inches **Body Width:** 0.688 inches **Body Height:** 0.844 inches **Unthreaded Mounting Hole Diameter:** 0.140 inches **Actuator Style:** Round **Actuator Diameter:** 0.094 inches **Actuator Free Position Height:** 3.480 inches **Actuator Adapter Style:** Pushbutton **Maximum Voltage Rating In Volts:** 600.0 ac and 250.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded hole Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

4.0 ounces

NSN 5930-01-150-8637

Sensitive Switch - Page 2 of 2

No Fiig: A053a0



Switch Actuating Force:
Between 9.0 ounces and 13.0 ounces
Actuator Movement:
0.015 pretravel inches and 0.005 overtravel inches and 0.002 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 2.000 amperes resistive ac
Thread Series Designator:
Uns
Terminal Type And Quantity:
3 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: