

View Online at <https://aerobasegroup.com/nsn/5930-01-151-4328>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Fungus proof

Body Diameter:

0.630 inches

Bushing Length:

0.440 inches

Body Length:

1.290 inches

Actuator Length:

0.630 inches

Actuator Style:

Rectangular

Actuator Width:

0.630 inches

Actuator Color:

Black single actuator

Illuminated Actuator Color:

White single actuator

Actuator Inscription:

Clear single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Rfi shielding

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.500 amperes inductive dc and 1.000 amperes lamp dc and 2.000 amperes resistive ac and 1.500 amperes inductive ac and 1.000 amperes lamp ac

Thread Series Designator:

Unef

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0