

View Online at <https://aerobasegroup.com/nsn/5930-01-151-4637>

Thread Class:

2b all threaded hole

Hazardous Locations/environmental Protection:

Dustproof

Overall Height:

1.080 inches

Body Height:

0.750 inches

Overall Diameter:

1.340 inches

Pressure Switch Type:

Absolute

Mounting Facility Circle Radius:

1.000 inches

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 250.0 degrees fahrenheit

Mounting Method:

Surface and threaded hole

Features Provided:

Automatic reset

Thready Qty Per Inch (tpi):

40 all threaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.112 inches all threaded hole

Mounting Facility Pattern:

Three position circular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Turret

Contact Load Current Rating:

5.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point adjustable, preset and deactuation point adjustable, preset

Contact Adjustment Range:

+0.50/+15.00 actuation point pounds per square inch absolute and +0.50/+15.00 deactuation point pounds per square inch absolute

Contact Stimulus Rating:

1.00 differential point pounds per square inch absolute

Contact Voltage Rating In Volts:

28.0 dc at sea level third voltage

Media For Which Designed:

Gas or liquid

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0