## NSN 5930-01-151-4640

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-151-4640

### **Inside Diameter:**

0.125 inches single connection

## **Overall Length:**

3.542 inches

## **Outside Diameter:**

0.213 inches single connection and 0.219 inches single connection

#### **Overall Height:**

2.891 inches

#### **Body Diameter:**

3.219 inches

#### **Body Height:**

2.324 inches

**Unthreaded Mounting Hole Diameter:** 

#### 0.218 inches

**Distance Between Mounting Facility Centers:** 

## 0.625 inches

Pressure Switch Type:

Gage

#### **Mounting Method:**

Bracket and unthreaded hole

## **Contact Action Stimulus:**

Increase

#### Mounting Facility Pattern:

Two position in-line

#### **Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

#### **Terminal Type:**

Quick disconnect, male

#### **Contact Load Current Rating:**

10.0 amperes resistive load first voltage

#### **Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

#### **Contact Stimulus Rating:**

2.50 actuation point inches of water and 1.50 deactuation point inches of water and 1.00 differential point inches of water

#### **Contact Voltage Rating In Volts:**

250.0 ac at sea level first voltage

#### Media For Which Designed:

Gas or liquid

## **Precious Material And Location:**

Terminal surfaces silver

## **Precious Material:**

Silver

# NSN 5930-01-151-4640

Pressure Switch - Page 2 of 2

Style Designator:

Cylindrical

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A048b0

