

View Online at <https://aerobasegroup.com/nsn/5930-01-151-4777>

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

3.520 inches

Overall Height:

1.740 inches

Overall Width:

2.120 inches

Unthreaded Mounting Hole Diameter:

0.189 inches single mounting facility

Individual Section Quantity:

2

Knob Manufacturer Code:

27192

Knob Manufacturer Part Number:

53-1160

Knob Specificational Markings:

Normal jog

Longest Horizontal Distance Between Mounting Centers:

1.620 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.250 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Unthreaded hole single mounting facility

Features Provided:

Actuator knob and cam actuated

Contact Voltage Rating In Volts:

440.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Cam Actuated Switch Contact Arrangement:

1 pole, double throw, both positions maintained each switch each section in-line

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section in-line

Contact Load Current Rating:

750.0 milliamperes resistive load highest ac voltage rating at sea level

Style Designator:

In-line, cam actuated

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0