## NSN 5930-01-151-6544

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-151-6544

| Body Style:   |  |  |  |
|---|--|--|--|
| Bushing mounted   |  |  |  |
| Overall Length:   |  |  |  |
| 1.070 inches  |  |  |  |
| Overall Height:   |  |  |  |
| 0.360 inches  |  |  |  |
| Overall Width:  |  |  |  |
| 0.360 inches  |  |  |  |
| Body Diameter:  |  |  |  |
| 0.360 inches  |  |  |  |
| Bushing Length:   |  |  |  |
| 0.250 inches  |  |  |  |
| Body Length:  |  |  |  |
| 0.500 inches  |  |  |  |
| Actuator Diameter:  |  |  |  |
| 0.187 inches  |  |  |  |
| Actuator Height:  |  |  |  |
| 0.187 inches  |  |  |  |
| Actuator Color:   |  |  |  |
| Green single actuator   |  |  |  |
| Illuminated Actuator Color:   |  |  |  |
| Green single actuator   |  |  |  |
| Maximum Voltage Rating In Volts:  |  |  |  |
| 230.0 ac  |  |  |  |
| Inclosure Type:   |  |  |  |
| Fully enclosed  |  |  |  |
| Mounting Method:  |  |  |  |
| Threaded bushing  |  |  |  |
| Thready Qty Per Inch (tpi):   |  |  |  |
| 40  |  |  |  |
| Thread Size:  |  |  |  |
| 0.250 inches  |  |  |  |
| Nonpile-up Contact Arrangement:   |  |  |  |
| 1 pole, single throw, normally open, double make, momentary action single switch unit |  |  |  |
| Contact Load Current Rating At Maximum Rated Voltage:                                 |  |  |  |
| 50.000 milliamperes resistive ac  |  |  |  |
| Special Features:   |  |  |  |
| Light-emitting diode  |  |  |  |
| Precious Material And Location:   |  |  |  |
| Terminal surfaces gold  |  |  |  |
| Thread Series Designator:   |  |  |  |
| Uns   |  |  |  |

## NSN 5930-01-151-6544

Push Switch - Page 2 of 2



| Termina     | I Type | And C  | Quantity: |
|-------------|--------|--------|-----------|
| ı Cı illili | IIVDE  | Allu V | zuannıv.  |

4 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0