NSN 5930-01-151-7458

Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-151-7458

Thread	Cla	ass:
--------	-----	------

2b single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

0.480 inches

Overall Height:

2.050 inches

Overall Width:

1.800 inches

Distance Between Mounting Facility Centers:

1.562 inches single mounting facility

Individual Section Quantity:

1

Mounting Method:

Threaded hole single mounting facility

Actuator Type:

Double push button single actuator

Thready Qty Per Inch (tpi):

56 single mounting facility

Thread Size:

0.086 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

16 single actuator

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9, a, b, c, d, e, f single section

Contact Arrangement Truth Table:

Bcd with complement, 1 pole - 16 positions single section

Color:

White single indicator background

Style Designator:

Rectangular indicating

Thread Series Designator:

Unc single mounting facility

NSN 5930-01-151-7458

Code Indicating Wheel Switch - Page 2 of 2



She	lf I	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0