

View Online at <https://aerobasegroup.com/nsn/5930-01-152-0142>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Salt spray resistant and shock resistant

**Overall Length:**

0.469 inches

**Overall Height:**

1.281 inches

**Overall Width:**

0.469 inches

**Body Diameter:**

0.469 inches

**Bushing Length:**

0.281 inches

**Body Length:**

0.547 inches

**Actuator Style:**

Round

**Actuator Height:**

0.328 inches

**Actuator Position-action Relationship:**

Up position momentary and down position maintained

**Maximum Voltage Rating In Volts:**

120.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

0.672 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes resistive dc and 1.000 amperes inductive dc and 500.000 milliamperes lamp dc and 3.000 amperes resistive ac and 1.000 amperes inductive ac and 500.000 milliamperes lamp ac

**Precious Material And Location:**

Contact surfaces silver

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0