

View Online at <https://aerobasegroup.com/nsn/5930-01-152-0142>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Salt spray resistant and shock resistant

Overall Length:

0.469 inches

Overall Height:

1.281 inches

Overall Width:

0.469 inches

Body Diameter:

0.469 inches

Bushing Length:

0.281 inches

Body Length:

0.547 inches

Actuator Style:

Round

Actuator Height:

0.328 inches

Actuator Position-action Relationship:

Up position momentary and down position maintained

Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

0.672 inches

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 1.000 amperes inductive dc and 500.000 milliamperes lamp dc and 3.000 amperes resistive ac and 1.000 amperes inductive ac and 500.000 milliamperes lamp ac

Precious Material And Location:

Contact surfaces silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0