

View Online at <https://aerobasegroup.com/nsn/5930-01-152-0144>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant and watertight

Overall Length:

1.949 inches

Overall Height:

0.500 inches

Overall Width:

0.500 inches

Body Diameter:

0.375 inches

Bushing Length:

0.644 inches

Body Length:

1.161 inches

Actuator Style:

Round

Actuator Diameter:

0.153 inches

Actuator Height:

0.144 inches

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

2350-01-017-2113

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing

Thread Size:

0.375 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.4 ounces

Switch Actuating Force:

104.0 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.125 overtravel inches and 0.010 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 3.000 amperes inductive dc and 2.000 amperes lamp dc

Thread Series Designator:

Unef

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0