## NSN 5930-01-152-5062

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-152-5062

**Thread Length:** 

0.250 inches single mounting facility

**Overall Length:** 

1.292 inches

First Flat Length:

0.250 inches single actuator

**Shaft Diameter:** 

0.123 inches single actuator and 0.126 inches single actuator

**Shaft Length:** 

0.375 inches single actuator

**Overall Diameter:** 

0.500 inches

**Individual Section Quantity:** 

1

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

1 single section rear

**Throw Quantity:** 

3 single section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:** 

30.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

3 single actuator

**Shaft Type:** 

Round, flatted single actuator

**Terminal Type:** 

Printed circuit

**Contact Switching Action:** 

Breaks before makes single section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

**Contact Load Current Rating:** 

200.0 milliamperes resistive load dc at sea level and 30.0 milliamperes inductive load dc at sea level and 100.0 milliamperes lamp load dc at

sea level

Style Designator:

Tap, circular, bushing mount

## NSN 5930-01-152-5062

Rotary Switch - Page 2 of 2



Thread Series Designato	TI	nread	Series	Design	ator
-------------------------	----	-------	--------	--------	------

Unf single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0