NSN 5930-01-152-6904

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-152-6904

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight and oiltight

Case Material:

Metal

Housing Height:

2.438 inches

Housing Length:

4.844 inches

Housing Width:

2.375 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

4.219 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.812 inches

Maximum Voltage Rating In Volts:

600.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Switch Actuating Force:

224.0 inch-ounces

Actuator Movement:

10.0 pretravel degrees and 28.0 overtravel degrees and 8.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

1.500 amperes resistive dc and 5.000 amperes resistive ac

Special Features:

Excludes actuator

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0