

View Online at <https://aerobasegroup.com/nsn/5930-01-152-6917>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

5.188 inches

Overall Height:

5.406 inches

Overall Width:

2.812 inches

Body Height:

2.750 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Mounting Facility Centers:

2.406 inches

Capillary Tube Length:

48.0 inches

Bulb Length:

3.625 inches

Bulb Diameter:

0.688 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Operating Temperature Rating:

385.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

1.0 amperes inductive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+280.00/+360.00 actuation point degrees fahrenheit and +280.00/+360.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point hex nut and external actuation point hex nut

Contact Voltage Rating In Volts:

115.0 dc at sea level second voltage

Media For Which Designed:

Liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0