NSN 5930-01-152-8016

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-152-8016

| · · |
|--|
| Body Style: |
| Panel mount |
| Hazardous Locations/environmental Protection: |
| Shock resistant and vibration resistant |
| Overall Length: |
| 0.750 inches |
| Overall Height: |
| 2.750 inches |
| Overall Width: |
| 0.750 inches |
| Body Length: |
| 0.688 inches |
| Body Width: |
| 0.750 inches |
| Actuator Length: |
| 0.620 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.090 inches |
| Actuator Width: |
| 0.620 inches |
| Actuator Color: |
| White single actuator |
| Illuminated Actuator Color: |
| White single actuator |
| Actuator Inscription: |
| Reset single actuator |
| Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Nonpile-up Contact Arrangement: |
| 3 pole, double throw, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 1.000 amperes resistive dc and 500.000 milliamperes inductive dc |
| Precious Material And Location: |
| Contacts gold |
| Torminal Type And Overtity: |

Terminal Type And Quantity:

9 turret and 5 tab, solder lug

NSN 5930-01-152-8016

Push Switch - Page 2 of 2



| C | ha | Ιf | 1 | ife | |
|---|-----|----|---|-------|--|
| • | ııe | | _ | .II C | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0