Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-153-0126

| Hazardous Locations/environmental Protection: |
|--|
| Dustproof |
| Overall Length: |
| 5.376 inches |
| Overall Height: |
| 2.906 inches |
| Overall Width: |
| 2.812 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.221 inches single mounting facility |
| Individual Section Quantity: |
| 2 |
| Knob Manufacturer Code: |
| 82121 |
| Knob Manufacturer Part Number: |
| D |
| Longest Horizontal Distance Between Mounting Centers: |
| 2.000 inches single mounting facility |
| Shortest Horizontal Distance Between Mounting Centers: |
| 1.000 inches single mounting facility |
| Longest Vertical Distance Between Mounting Centers: |
| 2.188 inches single mounting facility |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 2 each section rear |
| Throw Quantity: |
| 1 each section rear |
| Mounting Method: |
| Unthreaded hole single mounting facility |
| Features Provided: |
| Actuator knob |
| Contact Voltage Rating In Volts: |
| 600.0 ac at sea level |
| Switch Actuator Momentary Position: |
| Clockwise single actuator and counterclockwise single actuator |
| Mounting Facility Pattern: |
| Isosceles triangle single mounting facility |
| Switch Actuator Indexing Position Quantity: |
| 3 single actuator |
| Terminal Type: |
| Tab w/screw |
| |

NSN 5930-01-153-0126

Rotary Switch - Page 2 of 2



Contact Switching Action: Breaks before makes each section rear Switch Actuator Positioning Increment: 45.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 20.0 amperes resistive load ac at sea level Style Designator: Tap, circuit selector Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0