## NSN 5930-01-153-2408

**Hazardous Locations/environmental Protection:** 

Push Switch - Page 1 of 2

**Body Style:** Panel mount



View Online at https://aerobasegroup.com/nsn/5930-01-153-2408

Explosion proof
Overall Length:
0.750 inches
Overall Height:
3.660 inches
Overall Width:
0.750 inches
Body Length:
0.679 inches
Body Width:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.100 inches
Actuator Width:
0.620 inches
Actuator Color:
Red single actuator
Illuminated Actuator Color:
Red single actuator
Actuator Inscription:
Dop sel single actuator
Maximum Voltage Rating In Volts:
28.0 dc
End Application:
1520-01-088-3669
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Holding solenoid
Nonpile-up Contact Arrangement:
4 pole, double throw, both positions maintained single switch unit

## NSN 5930-01-153-2408

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc

**Precious Material And Location:** 

Contacts silver

**Terminal Type And Quantity:** 

17 socket, integrated wire termination

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0