

View Online at <https://aerobasegroup.com/nsn/5930-01-153-2624>

Inside Diameter:

0.125 inches all connections

Overall Length:

3.062 inches

Body Length:

1.828 inches

Overall Diameter:

3.125 inches

Distance Between Mounting Facility Centers:

1.884 inches

End Application:

4240-01-105-5521 entrance, protective

Pressure Switch Type:

Differential

Mounting Method:

Base and threaded hole

Thready Qty Per Inch (tpi):

32 all threaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.190 inches all threaded hole

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

10.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+0.15/+1.25 actuation point inches of water and +0.15/+1.25 deactuation point inches of water

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

480.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded internal all connections

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0