NSN 5930-01-153-8320

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-153-8320

| D. J. O. J. | | | | | |
|--|--|--|--|--|--|
| Body Style: | | | | | |
| Panel mount | | | | | |
| Hazardous Locations/environmental Protection: | | | | | |
| Explosion proof | | | | | |
| Overall Length: | | | | | |
| 0.688 inches | | | | | |
| Overall Height: | | | | | |
| 2.750 inches | | | | | |
| Overall Width: | | | | | |
| 0.688 inches | | | | | |
| Body Length: | | | | | |
| 0.688 inches | | | | | |
| Body Width: | | | | | |
| 0.688 inches | | | | | |
| Actuator Length: | | | | | |
| 0.620 inches | | | | | |
| Actuator Style: | | | | | |
| Rectangular | | | | | |
| Actuator Height: | | | | | |
| 0.070 inches | | | | | |
| Actuator Width: | | | | | |
| 0.620 inches | | | | | |
| Actuator Color: | | | | | |
| White single actuator | | | | | |
| Illuminated Actuator Color: | | | | | |
| White single actuator | | | | | |
| Actuator Inscription: | | | | | |
| Hf 2 rcvr single actuator | | | | | |
| Maximum Voltage Rating In Volts: | | | | | |
| 28.0 dc | | | | | |
| Inclosure Type: | | | | | |
| Fully enclosed | | | | | |
| Mounting Method: | | | | | |
| Panel | | | | | |
| Nonpile-up Contact Arrangement: | | | | | |
| 3 pole, double throw, both positions maintained single switch unit | | | | | |
| Contact Load Current Rating At Maximum Rated Voltage: | | | | | |
| 1.000 amperes resistive dc and 500.000 milliamperes inductive dc | | | | | |
| Precious Material And Location: | | | | | |
| Contacts gold | | | | | |
| Terminal Type And Quantity: | | | | | |

9 turret and 5 tab, solder lug

NSN 5930-01-153-8320

Push Switch - Page 2 of 2



| C | ha | Ιf | 1 | ife | |
|---|-----|----|---|-------|--|
| • | ııe | | _ | .II C | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0