NSN 5930-01-153-9370

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-153-9370

| Body Style: |
|--|
| Bushing mount |
| Overall Length: |
| 0.850 inches |
| Overall Height: |
| 1.391 inches |
| Overall Width: |
| 0.500 inches |
| Bushing Length: |
| 0.350 inches |
| Body Length: |
| 0.850 inches |
| Body Width: |
| 0.500 inches |
| Body Height: |
| 0.475 inches |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.115 inches |
| Actuator Height: |
| 0.410 inches |
| Actuator Position-action Relationship: |
| Up position maintained and down position maintained |
| Maximum Voltage Rating In Volts: |
| 120.0 ac and 28.0 dc |
| Mounting Surface To Terminal End Distance: |
| 0.631 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Thready Qty Per Inch (tpi): |
| 40 |
| Thread Size: |
| 0.250 inches |
| Nonpile-up Contact Arrangement: |
| 4 pole, double throw, both positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 5.000 amperes resistive ac

Precious Material And Location:

Terminal surfaces gold and contacts silver

NSN 5930-01-153-9370 Toggle Switch - Page 2 of 2



| Inread Series Designator: |
|-----------------------------|
| Uns |
| Terminal Type And Quantity: |
| 12 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A053a0