NSN 5930-01-154-0548

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-154-0548

| Overall Height: |
|---|
| 2.125 inches |
| Body Diameter: |
| 5.750 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.219 inches |
| Distance Between Mounting Facility Centers: |
| 2.000 inches |
| Capillary Tube Length: |
| 72.0 inches |
| Bulb Length: |
| 3.000 inches |
| Bulb Diameter: |
| 0.688 inches |
| Tempurature Sensing Element Type: |
| Capillary tube-bulb |
| Operating Tempurature Rating: |
| 220.0 degrees fahrenheit |
| Mounting Method: |
| Bracket and unthreaded hole |
| Features Provided: |
| Tubing end seal connection |
| Contact Action Stimulus: |
| Increase |
| Mounting Facility Pattern: |
| Two position in-line |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally closed, momentary action |
| Terminal Type: |
| Screw |
| Contact Load Current Rating: |
| 5.0 amperes resistive load second voltage |
| Contact Adjustability: |
| Actuation point adjustable and deactuation point adjustable |
| Contact Adjustment Range: |
| +100.00/+200.00 actuation point degrees fahrenheit and +100.00/+200.00 deactuation point degrees fahrenheit |
| Contact Adjustment Type: |
| External deactuation point screw and external actuation point knob |
| Contact Voltage Rating In Volts: |
| 230.0 dc at sea level fourth voltage |
| Media For Which Designed: |

Gas or liquid

NSN 5930-01-154-0548

Thermostatic Switch - Page 2 of 2



| Style Designator: |
|-------------------|
| Disc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No Fiig: A048b0