

View Online at <https://aerobasegroup.com/nsn/5930-01-154-0550>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

2.000 inches

**Overall Height:**

1.105 inches

**Body Diameter:**

Between 0.910 inches and 0.930 inches

**Mounting Slot Width:**

0.250 inches

**Body Height:**

Between 0.366 inches and 0.396 inches

**Distance Between Mounting Facility Centers:**

Between 1.625 inches and 1.688 inches

**End Application:**

Force provider

**Temperature Sensing Element Type:**

Internal sensor

**Operating Temperature Rating:**

350.0 degrees fahrenheit

**Mounting Method:**

Bracket and slot

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Terminal Type:**

Quick disconnect, male

**Contact Load Current Rating:**

6.0 amperes resistive load second voltage and 6.0 amperes inductive load second voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

135.00 actuation point degrees fahrenheit and 125.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

277.0 ac at sea level first voltage

**Media For Which Designed:**

Gas

**Style Designator:**

Disc w/flange

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0