## NSN 5930-01-154-0934

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-154-0934					
Hazardous Locations/environmental Protection:					
Explosion proof					
Overall Length:					
5.438 inches					
Overall Height:					
3.500 inches					
Overall Width:					
5.094 inches					
Unthreaded Mounting Hole Diameter:					
0.266 inches					
Distance Between Mounting Facility Centers:					
4.875 inches					
End Application:					
4920-01-024-6749, test stand, fuel noz					
Pressure Switch Type:					
Gage					
Mounting Method:					
Bracket and unthreaded hole					
Contact Action Stimulus:					
Decrease					
Proof Pressure:					
10.00 pounds per square inch gage					
Mounting Facility Pattern:					
Two position in-line					
Nonpile-up Contact Arrangement:					
1 pole, double throw, one position momentary					
Terminal Type:					
Screw					
Contact Load Current Rating:					
15.0 amperes resistive load third voltage					
Contact Adjustability:					
Actuation point adjustable					
Contact Adjustment Range:					
+0.07/+0.15 actuation point inches of water					

**Contact Adjustment Type:** 

External actuation point screw

**Contact Voltage Rating In Volts:** 

480.0 ac at sea level third voltage

**Media For Which Designed:** 

Liquid

Style Designator:

Cylindrical w/lugs

## NSN 5930-01-154-0934

Pressure Switch - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0