

View Online at <https://aerobasegroup.com/nsn/5930-01-154-0934>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

5.438 inches

Overall Height:

3.500 inches

Overall Width:

5.094 inches

Unthreaded Mounting Hole Diameter:

0.266 inches

Distance Between Mounting Facility Centers:

4.875 inches

End Application:

4920-01-024-6749, test stand, fuel noz

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Decrease

Proof Pressure:

10.00 pounds per square inch gage

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load third voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+0.07/+0.15 actuation point inches of water

Contact Adjustment Type:

External actuation point screw

Contact Voltage Rating In Volts:

480.0 ac at sea level third voltage

Media For Which Designed:

Liquid

Style Designator:

Cylindrical w/lugs

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0