NSN 5930-01-154-0937

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-154-0937

| liilength: |
|--|
| 5.375 inches |
| Overall Height: |
| 8.313 inches |
| Overall Width: |
| 2.500 inches |
| Body Diameter: |
| 0.687 inches |
| Body Length: |
| 4.781 inches |
| Body Width: |
| 2.500 inches |
| Body Height: |
| 2.944 inches |
| Overall Diameter: |
| 3.125 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.406 inches |
| Distance Between Mounting Facility Centers: |
| 2.750 inches |
| End Application: |
| Emd model gmeqr8645e6 and gmeql8-645-e6 diesel engines aboard 180 ft class coast guard vessels |
| Tempurature Sensing Element Type: |
| Bulb |
| Mounting Method: |
| Flange and unthreaded hole |
| Contact Action Stimulus: |
| Increase |
| Mounting Facility Pattern: |
| Two position in-line |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, both positions maintained |
| Terminal Type: |
| Screw |
| Contact Load Current Rating: |
| 16.0 amperes resistive load third voltage |
| Contact Adjustability: |
| Deactuation point adjustable and actuation point adjustable |

+85.00/+98.00 actuation point degrees fahrenheit and +85.00/+98.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

Contact Adjustment Range:

External deactuation point screw and external actuation point screw

NSN 5930-01-154-0937

Thermostatic Switch - Page 2 of 2



Contact Voltage Rating In Volts: 24.0 dc at sea level third voltage Special Features: Push to test button Frequency In Hertz: 60.0 first voltage Media For Which Designed: Gas or liquid Style Designator: Rectangular Shelf Life: N/a

Demilitarization:

Unit Of Measure:

Yes - demil/mli

Fiig:

A048b0