## NSN 5930-01-154-0941

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-154-0941

Overall Length:
4.938 inches
Overall Height:
2.750 inches
Overall Width:
2.875 inches
Body Length:
4.500 inches
Body Height:
2.750 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Shortest Horizontal Distance Between Mounting Centers:
0.656 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
Tempurature Sensing Element Type:
Bulb
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Isosceles triangle
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
9.6 amperes resistive load third voltage
Contact Adjustability:
Deactuation point adjustable, preset and actuation point adjustable, preset
Contact Adjustment Range:
+150.00/+225.00 actuation point degrees fahrenheit and +150.00/+225.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

165.00 actuation point degrees fahrenheit and 157.00 deactuation point degrees fahrenheit

## NSN 5930-01-154-0941

Thermostatic Switch - Page 2 of 2



Contact	Voltage Ra	iting In	Volts:
550.0 dc	at sea leve	l fourth	voltage

Frequency In Hertz:

60.0 second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/mounting lugs

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0