## NSN 5930-01-154-0951

Push Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-154-0951



**Body Style:** 

Panel mounted

Hazardous Locations/environmental Protection:

Explosion proof

**Overall Length:** 

0.688 inches

**Overall Height:** 

2.750 inches

**Overall Width:** 

0.688 inches

**Body Width:** 

0.688 inches

**Body Height:** 

0.688 inches

Actuator Length:

## 0.620 inches

Actuator Style:

Rectangular

Actuator Height:

0.070 inches

Actuator Width:

0.620 inches

Actuator Color:

White single actuator

**Illuminated Actuator Color:** 

White single actuator

**Actuator Inscription:** 

Kg 36 spare 2 single actuator

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

5895-01-078-2522

Mounting Surface To Terminal End Distance:

2.620 inches

Inclosure Type:

Fully enclosed

**Mounting Method:** 

Panel

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes resistive dc

## NSN 5930-01-154-0951

Push Switch - Page 2 of 2



Precious Material And Location:

Contacts gold

## Terminal Type And Quantity:

6 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0