## NSN 5930-01-154-2641

Slide Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-154-2641

Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Body Length:
1.500 inches
Body Width:
0.886 inches
Body Height:
0.875 inches
Unthreaded Mounting Hole Diameter:
0.125 inches
Switch Actuator Quantity:
1
Actuator Length:
0.250 inches
Actuator Height:
0.125 inches
Actuator Width:
0.250 inches
Actuator Position-action Relationship:
Center position momentary
Center position momentary  Maximum Voltage Rating In Volts:
Maximum Voltage Rating In Volts:
Maximum Voltage Rating In Volts: 28.0 dc
Maximum Voltage Rating In Volts: 28.0 dc End Application:
Maximum Voltage Rating In Volts: 28.0 dc End Application: P3-c acft
Maximum Voltage Rating In Volts: 28.0 dc End Application: P3-c acft Mounting Method:
Maximum Voltage Rating In Volts:  28.0 dc  End Application:  P3-c acft  Mounting Method:  Unthreaded hole
Maximum Voltage Rating In Volts:  28.0 dc  End Application:  P3-c acft  Mounting Method:  Unthreaded hole  Contact Load Current Rating At Maximum Rated Voltage:
Maximum Voltage Rating In Volts:  28.0 dc  End Application:  P3-c acft  Mounting Method:  Unthreaded hole  Contact Load Current Rating At Maximum Rated Voltage:  10.000 amperes lamp dc
Maximum Voltage Rating In Volts:  28.0 dc  End Application:  P3-c acft  Mounting Method:  Unthreaded hole  Contact Load Current Rating At Maximum Rated Voltage:  10.000 amperes lamp dc  Terminal Type And Quantity:
Maximum Voltage Rating In Volts:  28.0 dc  End Application:  P3-c acft  Mounting Method:  Unthreaded hole  Contact Load Current Rating At Maximum Rated Voltage:  10.000 amperes lamp dc  Terminal Type And Quantity:  2 pin
Maximum Voltage Rating In Volts:  28.0 dc  End Application:  P3-c acft  Mounting Method:  Unthreaded hole  Contact Load Current Rating At Maximum Rated Voltage:  10.000 amperes lamp dc  Terminal Type And Quantity:  2 pin  Shelf Life:
Maximum Voltage Rating In Volts:  28.0 dc  End Application: P3-c acft  Mounting Method: Unthreaded hole  Contact Load Current Rating At Maximum Rated Voltage:  10.000 amperes lamp dc  Terminal Type And Quantity: 2 pin  Shelf Life: N/a
Maximum Voltage Rating In Volts:  28.0 dc  End Application:  P3-c acft  Mounting Method: Unthreaded hole  Contact Load Current Rating At Maximum Rated Voltage:  10.000 amperes lamp dc  Terminal Type And Quantity:  2 pin  Shelf Life: N/a  Unit Of Measure:
Maximum Voltage Rating In Volts:  28.0 dc  End Application:  P3-c acft  Mounting Method:  Unthreaded hole  Contact Load Current Rating At Maximum Rated Voltage:  10.000 amperes lamp dc  Terminal Type And Quantity:  2 pin  Shelf Life:  N/a  Unit Of Measure:
Maximum Voltage Rating In Volts:  28.0 dc  End Application:  P3-c acft  Mounting Method: Unthreaded hole  Contact Load Current Rating At Maximum Rated Voltage:  10.000 amperes lamp dc  Terminal Type And Quantity: 2 pin  Shelf Life: N/a  Unit Of Measure:  Demilitarization: