

View Online at <https://aerobasegroup.com/nsn/5930-01-154-6287>

**Overall Length:**

3.880 inches

**Overall Diameter:**

4.120 inches

**End Application:**

4920-01-064-0600 test console

**Pressure Switch Type:**

Differential

**Operating Temperature Rating:**

Between 0.0 degrees celsius and 42.0 degrees celsius

**Mounting Method:**

Threaded bushing

**Features Provided:**

Electrical access port

**Thready Qty Per Inch (tpi):**

14 single threaded bushing

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.500 inches single threaded bushing

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

15.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point adjustable, preset and actuation point adjustable, preset

**Contact Adjustment Range:**

+0.50/+2.00 actuation point inches of water and +0.50/+2.00 deactuation point inches of water

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Stimulus Rating:**

0.50 actuation point inches of water and 0.10 deactuation point inches of water and 0.40 differential point inches of water

**Pressure Connector Type:**

Plain, threaded internal all connections

**Frequency In Hertz:**

60.0 single voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Ptf-sae short single threaded bushing

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0