NSN 5930-01-154-6294

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-154-6294

External deactuation point screw and external actuation point screw

Overall Length:
5.188 inches
Overall Width:
2.812 inches
Body Height:
2.750 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Capillary Tube Length:
120.0 inches
Bulb Length:
4.500 inches
Bulb Diameter:
0.375 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Shortest Horizontal Distance Between Mounting Centers:
0.656 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Isosceles triangle
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
9.6 amperes inductive load fourth voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+90.00/+165.00 actuation point degrees fahrenheit and +90.00/+165.00 deactuation point degrees fahrenheit
Contact Adjustment Type:

NSN 5930-01-154-6294

Thermostatic Switch - Page 2 of 2



Contact Voltage Rating In Volts: 550.0 dc at sea level third voltage Media For Which Designed: Gas or liquid Precious Material And Location: Contacts silver Precious Material: Silver Style Designator: Rectangular Shelf Life: N/a Unit Of Measure: --Demilitarization:

No Fiig: A048b0