

View Online at <https://aerobasegroup.com/nsn/5930-01-154-6297>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Water resistant

Overall Length:

0.510 inches

Overall Height:

1.280 inches

Overall Width:

0.510 inches

Bushing Length:

0.300 inches

Body Length:

0.510 inches

Body Width:

0.510 inches

Body Height:

0.410 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.120 inches

Actuator Height:

0.410 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

End Application:

5895-01-063-1916

Mounting Surface To Terminal End Distance:

0.570 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 3.000 amperes resistive ac

Precious Material And Location:

Terminal surfaces gold and contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0