NSN 5930-01-154-6306

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-154-6306

view Offilitie at https://aerobasegroup.com/hsh/osso-of-154-0soo
Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Shock proof
Overall Length:
0.740 inches
Overall Height:
3.060 inches
Overall Width:
0.740 inches
Body Length:
0.740 inches
Body Width:
0.740 inches
Case Material:
Metal
Actuator Length:
0.740 inches
Actuator Style:
Rectangular
Actuator Width:
0.740 inches
Actuator Color:
Red single actuator
Illuminated Actuator Color:
Red single actuator
Actuator Inscription:
Shut, down single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
4 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 ampere
inductive ac and 1.500 amperes lamp ac
Precious Material And Location:

Unable To Decode:

Unable to decode and unable to decode

Contact surfaces gold and contacts silver

NSN 5930-01-154-6306

Push Switch - Page 2 of 2



Terminal	Type	And	Quantity:
----------	------	-----	-----------

17 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0