NSN 5930-01-154-6309

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-154-6309

Body Style:					
Panel mount					
Hazardous Locations/environmental Protection:					
Explosion proof					
Overall Length:					
0.750 inches					
Overall Height:					
2.751 inches					
Overall Width:					
0.750 inches					
Body Length:					
0.688 inches					
Body Width:					
0.750 inches					
Case Material:					
Metal					
Actuator Length:					
0.620 inches					
Actuator Style:					
Rectangular					
Actuator Height:					
0.090 inches					
Actuator Width:					
0.620 inches					
Actuator Color:					
Red single actuator and red single actuator					
Illuminated Actuator Color:					
Red single actuator and red single actuator					
Actuator Inscription:					
Backup rcder off single actuator					
Maximum Voltage Rating In Volts:					
115.0 ac and 28.0 dc					
End Application:					
Sounding set, sonar an/bqn-17					
Inclosure Type:					
Fully enclosed					
Mounting Method:					
Panel					
Features Provided:					
Rfi shielding					
Nonpile-up Contact Arrangement:					
3 pole, double throw, both positions maintained single switch unit					

NSN 5930-01-154-6309

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

S	рe	cial	Fe	atu	res:
---	----	------	----	-----	------

Horizontal split lens

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

5 tab, solder lug and 9 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0