# NSN 5930-01-154-6309

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-154-6309

#### **Body Style:**

Panel mount

#### Hazardous Locations/environmental Protection:

Explosion proof

# **Overall Length:**

0.750 inches

#### **Overall Height:**

2.751 inches

#### **Overall Width:**

0.750 inches

#### **Body Length:**

0.688 inches

#### **Body Width:**

0.750 inches

#### Case Material:

Metal

# Actuator Length:

0.620 inches

# Actuator Style:

Rectangular

#### Actuator Height:

0.090 inches

#### Actuator Width:

0.620 inches

#### Actuator Color:

Red single actuator and red single actuator

#### Illuminated Actuator Color:

Red single actuator and red single actuator

#### Actuator Inscription:

Backup rcder off single actuator

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### **End Application:**

Sounding set, sonar an/bqn-17

#### Inclosure Type:

Fully enclosed

## **Mounting Method:**

Panel

#### **Features Provided:**

Rfi shielding

#### **Nonpile-up Contact Arrangement:**

3 pole, double throw, both positions maintained single switch unit

# NSN 5930-01-154-6309

Push Switch - Page 2 of 2



## Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes

inductive ac and 2.000 amperes lamp ac

#### **Special Features:**

Horizontal split lens

# Precious Material And Location:

Contacts silver

#### **Terminal Type And Quantity:**

5 tab, solder lug and 9 turret

#### Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A053a0