# NSN 5930-01-154-7428

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-154-7428

# **Body Style:**

Panel mount

## Hazardous Locations/environmental Protection:

Explosion proof

# **Overall Length:**

0.750 inches

## **Overall Height:**

2.751 inches

#### **Overall Width:**

0.750 inches

#### **Body Length:**

0.688 inches

## **Body Width:**

0.750 inches

#### Case Material:

Metal

# Actuator Length:

0.620 inches

# Actuator Style:

Rectangular

#### Actuator Height:

0.090 inches

# Actuator Width:

0.620 inches

# Actuator Color:

Red single actuator and red single actuator

#### **Illuminated Actuator Color:**

Red single actuator and red single actuator

#### **Actuator Inscription:**

Non secure selected single actuator

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### **End Application:**

Sounding set, sonar an/bqn-17

# Inclosure Type:

Fully enclosed

# **Mounting Method:**

Panel

# **Features Provided:**

Rfi shielding

# Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

# NSN 5930-01-154-7428

Push Switch - Page 2 of 2



# Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes

inductive ac and 2.000 amperes lamp ac

# **Special Features:**

Horizontal split lens

Precious Material And Location:

Contacts silver

# **Terminal Type And Quantity:**

5 tab, solder lug and 6 turret

# Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A053a0