NSN 5930-01-154-7429

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-154-7429

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
0.750 inches
Overall Height:
2.751 inches
Overall Width:
0.750 inches
Body Length:
0.688 inches
Body Width:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.090 inches
Actuator Width:
0.620 inches
Actuator Color:
Red single actuator and red single actuator
Illuminated Actuator Color:
Red single actuator and red single actuator
Actuator Inscription:
Secure short pls selected single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
Sounding set, sonar an/bqn-17
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Rfi shielding
Nonpile-up Contact Arrangement:
O and a development of the control o

2 pole, double throw, one position momentary single switch unit

NSN 5930-01-154-7429

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

e,		ial	Fe	atu	ro	٠.
OL.)ec	ıaı	ге	atu	ır e:	S.

Horizontal split lens

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

6 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0