

View Online at <https://aerobasegroup.com/nsn/5930-01-154-8303>

liilength:

5.875 inches

Overall Height:

8.312 inches

Overall Width:

3.562 inches

Body Length:

4.625 inches

Body Height:

2.750 inches

Unthreaded Mounting Hole Diameter:

0.406 inches

Distance Between Mounting Facility Centers:

2.750 inches

Bulb Length:

3.688 inches

Bulb Diameter:

0.688 inches

End Application:

Used with the immersion heater on an e.M.D. Diesel engine aboard 180 ft. Class coast guard vessels

Temperature Sensing Element Type:

Bulb

Mounting Method:

Flange and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Terminal Type:

Screw

Contact Load Current Rating:

16.0 amperes resistive load third voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+160.00/+170.00 actuation point degrees fahrenheit and +160.00/+170.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

24.0 dc at sea level third voltage

Special Features:

Push to test button

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A048b0