NSN 5930-01-154-8303

Thermostatic Switch - Page 1 of 2

24.0 dc at sea level third voltage



View Online at https://aerobasegroup.com/nsn/5930-01-154-8303

liilength:
5.875 inches
Overall Height:
8.312 inches
Overall Width:
3.562 inches
Body Length:
4.625 inches
Body Height:
2.750 inches
Unthreaded Mounting Hole Diameter:
0.406 inches
Distance Between Mounting Facility Centers:
2.750 inches
Bulb Length:
3.688 inches
Bulb Diameter:
0.688 inches
End Application:
Used with the immersion heater on an e.M.D. Diesel engine aboard 180 ft. Class coast guard vessels
Tempurature Sensing Element Type:
Bulb
Mounting Method:
Flange and unthreaded hole
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained
Terminal Type:
Screw
Contact Load Current Rating:
16.0 amperes resistive load third voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+160.00/+170.00 actuation point degrees fahrenheit and +160.00/+170.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
External deactuation point screw and external actuation point screw
Contact Voltage Rating In Volts:

NSN 5930-01-154-8303

Thermostatic Switch - Page 2 of 2



Special Features:
Push to test button
Frequency In Hertz:
60.0 first voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A048b0