

View Online at <https://aerobasegroup.com/nsn/5930-01-154-9862>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Actuator Length:

1.500 inches

Actuator Style:

Roller arm

Actuator Height:

1.000 inches

Actuator Roller Diameter:

0.750 inches

Actuator Roller Width:

0.250 inches

Housing Height:

2.250 inches

Housing Length:

2.250 inches

Housing Width:

2.438 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

1.812 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

4.214 inches

Maximum Voltage Rating In Volts:

600.0 ac

End Application:

Overspeed limit switch used on an e.M.D. Diesel engine model nos. Gmeqr8645e6 and gmeql8645e6 aboard 180 ft class coast guard vessels

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

128.0 ounces

Actuator Movement:

14.0 pretravel degrees and 74.0 overtravel degrees and 12.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive ac

Special Features:

C w operation

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0