## NSN 5930-01-155-0744

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-155-0744

**Thread Class:** 

2a single pressure connection

**Thread Length:** 

0.675 inches single pressure connection

**Overall Length:** 

3.250 inches

**Outside Diameter:** 

0.750 inches single connection

**Overall Width:** 

2.165 inches

**Body Diameter:** 

1.870 inches

**Body Length:** 

2.125 inches

**Unthreaded Mounting Hole Diameter:** 

0.204 inches

**Distance Between Mounting Facility Centers:** 

0.500 inches

**Pressure Switch Type:** 

Gage

**Operating Tempurature Rating:** 

Between -66.0 degrees fahrenheit and 250.0 degrees fahrenheit

**Mounting Method:** 

Bracket and unthreaded hole

**Contact Action Stimulus:** 

Increase

**Proof Pressure:** 

260.00 pounds per square inch gage

**Thread Size:** 

0.750 inches single pressure connection

**Mounting Facility Pattern:** 

Two position in-line

**Nonpile-up Contact Arrangement:** 

1 pole, double throw, one position momentary

**Terminal Type:** 

Connector, receptacle

**Contact Load Current Rating:** 

2.0 amperes resistive load second voltage

**Contact Adjustability:** 

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:** 

5.50 actuation point pounds per square inch gage and 2.00 deactuation point pounds per square inch gage

## NSN 5930-01-155-0744

Pressure Switch - Page 2 of 2



## Contact Voltage Rating In Volts: 30.0 dc at sea level second voltage

**Pressure Connector Type:** 

Flared, threaded external single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical w/mounting lugs

**Thread Series Designator:** 

Unjf single pressure connection

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A048b0