NSN 5930-01-155-0744

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-155-0744

Thread Class:

2a single pressure connection

Thread Length:

0.675 inches single pressure connection

Overall Length:

3.250 inches

Outside Diameter:

0.750 inches single connection

Overall Width:

2.165 inches

Body Diameter:

1.870 inches

Body Length:

2.125 inches

Unthreaded Mounting Hole Diameter:

0.204 inches

Distance Between Mounting Facility Centers:

0.500 inches

Pressure Switch Type:

Gage

Operating Tempurature Rating:

Between -66.0 degrees fahrenheit and 250.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

260.00 pounds per square inch gage

Thread Size:

0.750 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

2.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

5.50 actuation point pounds per square inch gage and 2.00 deactuation point pounds per square inch gage

NSN 5930-01-155-0744

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts: 30.0 dc at sea level second voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical w/mounting lugs

Thread Series Designator:

Unjf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0