

View Online at <https://aerobasegroup.com/nsn/5930-01-155-0802>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

6.468 inches

Overall Height:

2.906 inches

Overall Width:

2.812 inches

Unthreaded Mounting Hole Diameter:

0.221 inches single mounting facility

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

2.000 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.188 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Features Provided:

Actuator knob and legend plate

Contact Voltage Rating In Volts:

600.0 ac at sea level

Switch Actuator Momentary Position:

Clockwise single actuator and counterclockwise single actuator

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section periphery

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

20.0 amperes resistive load ac at sea level

Precious Material And Location:

Contact and terminal surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiq:

A052b0