

View Online at <https://aerobasegroup.com/nsn/5930-01-155-1247>

Thread Class:

3a first pressure connection 2a second pressure connection

Overall Length:

3.340 inches

Overall Diameter:

0.875 inches

End Application:

3930-01-054-3833 truck, lift, fork

Pressure Switch Type:

Differential

Width Across Flats:

1.000 inches

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

Mounting Method:

Clamp

Features Provided:

Electrical box connector

Thready Qty Per Inch (tpi):

24 second pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

4500.00 pounds per square inch

Thread Size:

0.750 inches first pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load second voltage and 3.0 amperes inductive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

25.00 actuation point pounds per square inch and 40.00 deactuation point pounds per square inch and 15.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Pressure Connector Type:

Plain, threaded external all connections

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf first pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0