

View Online at <https://aerobasegroup.com/nsn/5930-01-155-1247>

**Thread Class:**

3a first pressure connection 2a second pressure connection

**Overall Length:**

3.340 inches

**Overall Diameter:**

0.875 inches

**End Application:**

3930-01-054-3833 truck, lift, fork

**Pressure Switch Type:**

Differential

**Width Across Flats:**

1.000 inches

**Operating Temperature Rating:**

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

**Mounting Method:**

Clamp

**Features Provided:**

Electrical box connector

**Thready Qty Per Inch (tpi):**

24 second pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

4500.00 pounds per square inch

**Thread Size:**

0.750 inches first pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

5.0 amperes resistive load second voltage and 3.0 amperes inductive load second voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

25.00 actuation point pounds per square inch and 40.00 deactuation point pounds per square inch and 15.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

**Pressure Connector Type:**

Plain, threaded external all connections

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Unf first pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0