

View Online at <https://aerobasegroup.com/nsn/5930-01-155-1250>

Thread Class:

2b single mounting facility

Thread Length:

0.250 inches 1st mounting facility

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

5.380 inches

Shaft Diameter:

0.375 inches single actuator

Individual Section Quantity:

2

Knob Manufacturer Code:

82121

Knob Manufacturer Part Number:

G

Longest Horizontal Distance Between Mounting Centers:

2.000 inches 2nd mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.000 inches 2nd mounting facility

Longest Vertical Distance Between Mounting Centers:

2.180 inches 2nd mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

3 each section rear

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Four position circular single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round single actuator

Criticality Code Justification:

Feat

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Special Features:

Item must comply with requirements of desc production standard no. L03288; for navy nuclear propulsion plant products only

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0